

Messing-Profile

Stablänge: **5 m**



**U-Profil
gleichschenkelig**
h x b x h x s Ms 58
F 45

Nr.	Abmessung	g/m
E30.2.162	8 x 8 x 8 x 1	187
E30.2.163	10 x 10 x 10 x 1	238
E30.2.165	15 x 15 x 15 x 2	700
E30.2.166	20 x 20 x 20 x 2	960



T-Profil
b x h x s Ms 58
F 45

Nr.	Abmessung	g/m
E30.2.175	10 x 10 x 1,5	236
E30.2.176	15 x 15 x 2	476
E30.2.177	20 x 20 x 2	646
E30.2.179	25 x 25 x 3	1200
E30.2.180	30 x 30 x 3	1400



Vierkantrohr
b x h x s Ms 58
F 45

Nr.	Abmessung	g/m
E30.2.265	6 x 6 x 1	170
E30.2.266	8 x 8 x 1	238
E30.2.267	10 x 10 x 1	306
E30.2.268	15 x 15 x 1	510
E30.2.269	20 x 20 x 1	646
E30.2.270	25 x 25 x 1	816
E30.2.271	30 x 30 x 1	986
E30.2.273	40 x 40 x 1	1330



**Winkelprofil
gleichschenkelig**
b x h x s Ms 58
F 45

Nr.	Abmessung	g/m
E30.2.182	10 x 10 x 1	162
E30.2.183	15 x 15 x 2	476
E30.2.184	20 x 20 x 2	646
E30.2.185	25 x 25 x 2	816
E30.2.186	15 x 15 x 3	690
E30.2.187	20 x 20 x 3	944
E30.2.188	25 x 25 x 3	1200
E30.2.189	30 x 30 x 3	1450
E30.2.190	35 x 35 x 3	1710
E30.2.191	40 x 40 x 3	1960
E30.2.193	30 x 30 x 4	1900
E30.2.195	40 x 40 x 4	2580
E30.2.196	50 x 50 x 4	3270



**Winkelprofil
ungleichschenkelig**
b x h x s Ms 58
F 45

Nr.	Abmessung	g/m
E30.2.199	20 x 10 x 2	480
E30.2.200	20 x 15 x 2	560
E30.2.201	25 x 15 x 2	650
E30.2.202	30 x 15 x 2	730
E30.2.204	25 x 15 x 3	940
E30.2.205	30 x 15 x 3	1000
E30.2.206	40 x 20 x 3	1500



Rechteckrohr
b x h x s Ms 58
F 45

Nr.	Abmessung	g/m
E30.2.274	16 x 8 x 1	360
E30.2.278	12 x 8 x 1	295
E30.2.275	20 x 10 x 1	485
E30.2.276	30 x 10 x 1	670
E30.2.277	50 x 13 x 1,5	1500

Stablängen betragen **5000 mm**.

Alle Profile sind im Zuschnitt erhältlich.

Diessner GmbH

Moritzstraße 29 0611 - 300 355
65185 Wiesbaden 0611 - 30 78 29
Email info@diessnergmbh.de
Internet www.diessnergmbh.de

Stand: 05.03.2017

Messing - Rundprofile

Stablänge: **1/3 m**

● Nr.	Rundprofil Ø Stablänge 3 m	Ms 58 F 45
	Abmessung	g/m
E31.2.210	1	7
E31.2.211	1,5	15
E31.2.212	2	27
E31.2.213	2,5	42
E31.2.214	3	60
E31.2.215	4	107
E31.2.216	5	167
E31.2.217	6	240
E31.2.218	7	324
E31.2.219	8	427
E31.2.220	9	541
Nr.	Abmessung	kg/m
E31.2.221	10	0,67
E31.2.222	11	0,81
E31.2.223	12	0,96
E31.2.224	13	1,13
E31.2.225	14	1,31
E31.2.226	15	1,50
E31.2.227	16	1,71
E31.2.228	17	1,93
E31.2.229	18	2,16
E31.2.230	19	2,41

● Nr.	Rundprofil Ø Stablänge 3 m	Ms 58 F 45
	Abmessung	g/m
E31.2.231	20	2,67
E31.2.232	21	2,94
E31.2.233	22	3,23
E31.2.234	23	3,55
E31.2.235	24	3,84
E31.2.236	25	4,16
E31.2.237	26	4,51
E31.2.238	27	4,88
E31.2.239	28	5,23
E31.2.240	30	6,00
E31.2.241	32	6,84
E31.2.242	35	8,19
E31.2.245	40	10,69
E31.2.246	42	11,70
E31.2.247	45	13,50
Ab hier Stablänge 1 m !		
E31.2.249	50	16,70
E31.2.250	60	24,00
E31.2.252	70	32,70
E31.2.253	80	42,70
E31.2.255	90	54,10
E31.2.256	100	66,70
E31.2.257	110	80,80
E31.2.258	120	96,10
E31.2.259	130	112,80
E31.2.260	140	130,82
E31.2.261	150	150,20



Die Stablängen der Rundrohre betragen **3000 mm**, bei Profilen größer Ø 50mm **1000 mm**.
Alle Profile sind im Zuschnitt erhältlich.